

First Dual-interface



Retail



Hospitality



Ticketing



Kiosk

3 inch POS Printer

SRP-350plusII

BIXOLON SRP-350plusII is a 3 inch thermal receipt printer to support your successful Business all the time. The SRP-350plusII is fully featured with improved printing speed up to 250mm/sec and Smart BIXOLON software package. Easy-to-use Windows driver and other various drivers make the SRP-350plusII even more flexible.



HIGHLIGHTS



Multiple interface choice

- Serial + USB
- Parallel + USB
- Ethernet + USB

Reliable Printing Performance

- A family of the steady-selling SRP-350 line
- Printing speed up to 250 mm/sec



BIXOLON[®]

a Better Solution for your Business™

3 inch POS Printer

SRP-350plusII



SPECIFICATIONS

Print Characteristics

Print Method

Direct Thermal

Print Speed

SRP-350plusII: 250 mm/sec

SRP-352plusII: 230 mm/sec

Print Resolution

SRP-350plusII: 180 dpi

SRP-352plusII: 203 dpi

Print Width

Up to 72 mm

Sensor

Paper End, Paper Near End, Cover Open

Media Characteristics

Media Type

Receipt

Media Width

80 mm

Media Roll Diameter

Up to 83 mm

Media Thickness

0.062 ~ 0.075 mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (WxLxD)

145 x 195 x 146 mm

(5.70 x 7.67 x 5.74 inch)

Weight

1.65 kg (3.63 lbs.)

Power

EnergyStar Certified,

External Power Adaptor 100-240V AV, 50/60Hz

Drawer Port

2 ports

Performance Characteristics

Memory

64 Mbit SDRAM, 16 Mbit FlashROM

NV Image Memory

256 Kbytes (mono)

128 Kbytes (color)

Receive Buffer

4 Kbytes

User Define Buffer

12 Kbytes

Interface

Dual Interface

Serial + USB 2.0 HS

Parallel + USB 2.0 HS

Ethernet + USB 2.0 HS

Environment Characteristics

Temperature

Operating: 0~45°C (32~113°F)

Storage: -20~60°C (-4~140°F)

Humidity

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

Reliability

Printer Unit (MCBF)

70 Million Lines

TPH

150 km

Auto Cutter

1.8 Million Cuts

Software

Emulation

BXL / POS

Driver / Utility

Windows Driver, OPOS Driver, JPOS Driver,

Linux CUPS Driver, Mac Driver,

Virtual COM USB/Ethernet Driver, Utility Program

SDK

iOS SDK, Android SDK

Fonts / Graphics / Symbologies

Character Size

Font A: 12x24 Font B: 9x17 Font C: 9x24

KOR, CHN, JPN: 24x24

Characters Per Line

SRP-350plusII: Font A: 42 Font B, C: 56

KOR, CHN, JPN: 21

SRP-352plusII: Font A: 48 Font B, C: 64

KOR, CHN, JPN: 24

Character Sets

Alphanumeric: 95

Extended Graphics: 128x37 page

International: 32

Graphics

Supporting user-defined fonts, graphics, formats, and logos

Barcode Symbologies

1D: Coda Bar, Code39, Code93, Code128, EAN-8, EAN-13, ITF, UPC-A, UPC-E

2D: PDF417, QR Code

BR-SRP-350plusII-EN-OCT13

Copyright © 2013 BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

BIXOLON®