

Hisense

HM388

8" Point of Sale Tablet



8" Tablet for Point of Sale Applications

Run your retail or hospitality business more efficiently with the stylish, reliable and space-saving HM388 POS Tablet with Windows® operating system. The 8 inch, bezel-free and wide screen display is designed with Projected Capacitive (PCAP) touch technology that helps to extend the operating life and allow multi-touch gesture control. Use the ports in the docking station to connect to a wide range of peripheral devices.

- 8" Wide Screen
- Bezel-Free, PCAP Multi-Touch Screen
- Standard Integrated Card Reader
- Standard Docking Station Includes I/O Expansion Ports



Bluetooth™



HM388 – 8" Point of Sale Tablet



Stylish, Space-Saving Tablet Includes Docking Station



Integrated Card Reader Standard



Standard Docking Station Includes I/O Expansion Ports

Features

- Front and Rear Cameras
- Integrated Card Reader
- 0.8 Watt Speaker
- LED Indicator
- Built-In Microphone Provides Sound Input While Making Web-Calls
- Capture a Front View Picture or Record Videos
- HM388 Rugged Tablet Includes a Built-In Battery
- Docking Station Includes Power Adaptor and Cord
- Compatible with Popular Standard Applications

Specifications

HM388

Processor:	Cherrytrail Z8350
Operating System:	Windows 10
Display:	8" TFT LCD (LED Back-Light)
Resolution:	1280 x 800
Brightness:	300 cd/m2
Touch Panel:	True-Flat Projected Capacitive Touch
Memory:	2GB RAM
Storage:	32GB eMMC
Camera –	Rear: 5 Megapixel Camera
	Front: 0.3 Megapixel Camera
Wireless –	Wi-Fi: WiFi802.11 b/g/n 2.4GHz
	Bluetooth: Integrated Bluetooth V4.0
Speaker:	8 Ohm, 0.8 Watt Speaker
Audio:	3.5mm Socket
MCR:	Standard Integrated Triple Track Card Reader
NFC:	Supports MIFARE one and MIFARE CPU Card
Battery –	Type: 4000mAh (3.8V)
	Life: 4 Hours
I/O Interface:	Micro-SD Slot / Micro-USB / Audio / Micro HDMI 1.4a
Tablet Connector:	7 Pin Pogo Style Connector
Docking Station –	I/O: Three USB 2.0 / COM1 (RJ45)
	DC Input: One DC Jack (5V)
Power Supply:	5V / 3A External Power Adaptor 100-240V 50/60Hz
Temperature –	Operating: 32° F to 104° F (0° C to 40° C)
	Storage: -4° F to 149° F (-20° C to 65° C)
Humidity –	Operating: 20% to 90% RH (Non-Condensing)
	Storage: 20% to 93% RH (Non-Condensing)
Dimensions –	Tablet: 10-7/8"W x 7-5/8"H x 7/8"D
	Tablet/Docking Station: 11"W x 6-5/8"H x 7-1/16"D
Safety and EMI:	FCC Class-B / CE Class-B / RoHS

Camera | Charging Indicator



Micro SD Card Slot

Speaker | Volume – | Volume + | Power | Camera



MCR | DC Jack | COM1 (RJ45) | USB | HDMI | Micro USB | DC Jack | Audio