

SNBC

Extraordinary
Value!

BTP-M300

Impact Receipt Printer



Contains Everything Necessary – Including the Communication Cables – in the Carton

Preferred for POS, Bar, Kitchen, and Data-Logging Printer Applications

The SNBC BTP-M300 produces clear, precise and archive-quality documents. It is ideal for requisitions and receipts including coupons, rebates and special offers. Featuring trouble free drop-and-print paper loading, the extraordinarily reliable M300 provides paper “pull” technology for jam-free operation and best-in-class cutter performance. The internal power supply eliminates unsightly and messy cords and bricks.

- Choose a USB or Ethernet On-Board Interface
- Serial, Parallel, USB, Ethernet, Bluetooth and WiFi Interfaces Options
- Cutter Rated for 1,800,000 Cuts
- Energy Star Certified
- SDK Available for iOS and Android Operating Systems



BTP-M300 Impact Receipt Printer



Drop and Print Paper Loading with Built-In Paper Width Selector



Optional Audio/Visual Print Messenger



Built-In Wall Mount Capability



Concealed, Yet Easy to Access Power Supply – Dual Interface Boards Allow a Variety of Configurations

Features

Proven impact printing technology preferred for POS kitchen printer and archivable receipt applications.

- Choose from USB or Ethernet on Board
- Serial, Parallel, Ethernet, USB, Bluetooth and Wireless WiFi Interface Boards Available
- Uses the Same Interface Boards as Most Other SNBC Printers
- Auto-Cutter with **Selectable** Full or Partial Cut (Tear Bar also Included)
- Two-Color Print – Uses Industry Standard ERC-38 Ribbon Cartridge
- Fast 4.7 Lines per Second Print Speed
- Drop and Print Paper Loading
- Stores and Prints Logo Images
- Built-In Wall Mount Capability
- Paper-End Sensor
- Adjustable Paper Near-End Sensor
- No Dip Switches
- Includes Starter Paper Roll, Paper Width Selector, Appropriate Communications Cables, Power Cord, Power Switch Cover, Ribbon and a CD-ROM with Drivers, Utilities and User's Manual

Optional Devices / Upgrades

Modify or upgrade your printer with these easy-to-add options:

- Serial, Parallel, Ethernet, Bluetooth and Wireless WiFi Interface Boards are User Interchangeable
- USB+Cash Drawer Port or Ethernet+Cash Drawer Port
- Audio/Visual Print Messenger – For Noisy Kitchens – Alarm Sounds and Light Flashes When a New Order is Printed

Ports and Connectivity

- 1 USB+Cash Drawer or Ethernet+Cash Drawer Versions Available
- 2 Choice of Serial (Shown), Parallel, USB, Ethernet, Bluetooth or Wireless WiFi Interface Boards Available

Standard configurations shown. Create other configurations by purchasing interface boards separately.

All product and company names are trademarks, service marks or registered trademarks of their respective owners. All features and specifications are subject to change without notice.

Specifications

Max. Print Speed:	4.7 Lines per Second / 19.6mm per Second
Printing Method:	Impact
Characters Per Line –	Font A: 33 / 35 Font B: 40 / 42
Characters Size –	Font A: 9 x 9 Font B: 7 x 9
Paper Roll Type –	Width: 80 / 76 / 69.5 / 57.5mm ± 0.5mm Maximum Diameter: 83mm Paper Thickness: 0.06mm ~ 0.085mm 2-Ply Paper Thickness: 0.05mm ~ 0.08mm Total ≤ 0.14mm Auto Paper Cutting Method: Auto-Cutter with Selectable Full or Partial Cut
Inking Supply:	ERC-38 Ribbon Cartridge (Black/Red)
Reliability –	MTBF: 180,000 Hours MCBF: 18,000,000 Lines Printhead Life: 150,000,000 Characters Cutter Life: 1,800,000 Cuts
Character Set –	Alphanumeric: 95 International: 37 Graphic: 128 x 12 Page / Traditional/Simplified Chinese / Thai / Japanese
Interpreter:	ESC/POST™
Interface –	Board 1: USB+Cash Drawer or Ethernet+Cash Drawer Board 2: Serial / Parallel / USB / Bluetooth / WiFi / Ethernet
Driver –	32 bit and 64 bit: Windows 8 / Windows 7 / Server 2008 / Server 2003 / Vista 32 bit: POSReady 2009 / 2000 Professional / 2000 Server / XP Home / XP Professional 64 bit: Windows XP Software Development Kit: iOS / Android
Drawer Port:	Up to 2 Drawers (+24VDC) / Supports Drawer Compulsion
Data Buffer – Receive Buffer RAM:	8 KB RAM
RAM Bitmap:	8 KB
Flash Bitmap:	128 KB
Power Supply:	24V DC ± 5% Internal Adapter Included
Current/Power Usage:	1.5A / 36W
Operating Temperature:	40° ~ 114°F (5° ~ 45°C)
Operating Humidity:	20% ~ 90% RH (Non-Condensing)
Dimensions:	6-1/4"W x 6"H x 9-1/2"D
Ship Weight:	9.0 lbs. (Each Unit) / 40 lbs. (Master Carton 4)
Safety and EMI:	FCC / RoHS

