

ER-650 Series

Value Priced Registers Loaded with POS System Features

- Adjustable Multi-Line Backlit Operator Screen
- RS-232C Ports Available for Point-of-Sale Options
- Inter-Register Communications Available for Store Wide Report Consolidation and Programming
- Heavy-Duty, All Metal Cash Drawer with Two Media Slots and 3-Position / 4-Function Lock
- Available in Three Different Configurations:
 - Fast, Quiet, Thermal or Plain Paper Dot-Matrix Printing
 - Flat, Spill-Resistant or Raised-Key Keyboards




ER-650
Flat, Spill-Resistant Keyboard;
Thermal Receipt Printer



ER-650R
Raised-Key Keyboard;
Thermal Receipt Printer



ER-655II
Flat, Spill-Resistant Keyboard;
Dot-Matrix Receipt Printer



PC INTERFACE CASH DRAWER PRINTER SLIP PRINTER COIN DISPENSER SCALE APPROVED POLE DISPLAY GRAPHIC DISPLAY KITCHEN VIDEO VIDEO SURVEILLANCE SCANNER LIQUOR DISPENSER INTEGRATED PAYMENT

Commercial Grade Construction, Long-Lasting and Serviceable **ER-650 Series**

Operator Screen

The operator screen clearly sets the ER-650 apart from traditional low-cost ECRs. Just glance at the screen to verify or fill an order. If necessary, you can page up or down through larger transactions. Easy-to-follow messages guide your operators with minimal training.

On-screen programming simplifies programming of new PLU items and price changes. Managers can access sales, inventory, and financial information and view it directly on the screen.

Flat, Spill-Resistant Keyboard

The 98 key keyboard is spill resistant and easy to clean. Each location is completely programmable to fit your menu and function requirements. Program your menu items easily by typing on a transparent alpha keyboard overlay.

If preferred, the ER-650R provides a traditional raised-key keyboard.

Thermal Printer

Keep pace with fast, quiet, thermal printing. Drop-in loading simplifies paper changing and virtually eliminates paper jamming. Choose the ER-655II if you prefer traditional plain paper dot-matrix printing.

Electronic Journal

The ER-650 stores your detailed sales journal in memory for printing at the end of the day. Electronic journal can be

printed in its entirety or select from ten different print option selections.

Communications Ready

Two RS-232C ports and inter-register communications (IRC) are available on every SAM4s ER-650! Using IRC, up to 8 registers can be connected for consolidating store wide reports and/or programming. Each RS-232C port can be connected to one of the following options: • Phone Modem or PC • Scanner • Scale • Remote Printer or Requisition Video • Coin Dispenser • Pole Display • Video Surveillance • Liquor Dispenser • DataTran™ Integrated Payment for Credit, Debit and Gift Card

Optional communications software, SAM650i, can be used to upload or download register data directly from a PC, or via a phone modem. Daily transaction details, as well as sales and financial reports can be uploaded to your PC for storage and/or further review.

Additional Features

- Up to 5 Price Levels for Each PLU
- Up to 5 PLU Modifier Keys
- Up to Approximately 10,000+ PLUs for Large Item or UPC Files
- 99 PLU Group Totals
- Operation for up to 99 Clerks with Separate Report Totals
- Built-In Electronic Time Clock
- Hard or Soft Check Tracking



Easy-to-Follow Messages Guide Your Operators with Minimal Training



Quick and Easy Drop-in Paper Loading (ER-650, ER-650R)



Integrated Payment Processing

With an optional DataTran™ credit terminal, you can process credit transactions using the printer, keyboard and display of the cash register. Processing both cash and credit transactions on your SAM4s ECR will improve security, reduce paperwork and will save time, counter space and supplies.

SPECIFICATIONS

	ER-650	ER-650R	ER-655II
Keyboard:	98 Key Flat	76 Key Raised	98 Key Flat
Display – Operator:	LCD (128 x 64 Dots)	LCD (128 x 64 Dots)	LCD (128 x 64 Dots)
Customer:	VFD (10 Digits)	VFD (10 Digits)	VFD (10 Digits)
Printer – Type:	Thermal	Thermal	Impact
Model:	SAM4s STM-210	SAM4s STM-210	SAM4s STM-310
Speed:	13.3 lps; (50mm/sec.)	13.3 lps; (50mm/sec.)	4.5 Lines per Second
Paper Roll:	2¼" (58mm) Thermal	2¼" (58mm) Thermal	2¼" (58mm)
Dimensions (WxDxH):	15¾" x 17¾" x 11½"	15¾" x 17¾" x 11½"	15¾" x 17¾" x 11½"
Shipping Weight:	32.10 lbs.	32.10 lbs.	32.10 lbs.
Power Requirements:	120V AC 60 Hz	120V AC 60 Hz	120V AC 60 Hz
Power Consumption:	15W Reg.; 28W Peak	15W Reg.; 28W Peak	15W Reg.; 28W Peak
Operation Temperature:	32°~113°F (0°~45°C)	32°~113°F (0°~45°C)	32°~113°F (0°~45°C)
Humidity Range:	30% to 80% RH	30% to 80% RH	30% to 80% RH
Memory Protection	Full Charge for 24 Hours Will Protect Memory for Approximately 60 Days		



All product features are subject to change without notice. All product and company names are trademarks, service marks or registered trademarks of their respective owners.